



Construction

Undertile Heating Cable consists of a resistance element provided with a primary insulation of fluoropolymer then covered with metal shielding and final outer sheath of PVC or Fluoropolymer.

Heating Element & OD : Single Conductor(2.3mm)

and Twin Conductor (3.2 mm)

Standard Wattage : 10 W/m @ 230V AC.

Maximum Wattage : 18 W/m @ 230V AC.

Cold Lead : 3.0 mtr

Features

Compliance	Standards: EN 60335 / EN 62233 / IEC 60800, CSA - C22.2 No.130, UL1683
Approvals	Intertek SEMKO, SGS Fimko, EAC & UL
Flexibility	Can be laid on any area, or any floor layout, as may be desired.
Reliability	A uniquely designed hot to cold junction makes the termination 100% foolproof.
Safety	Thermostats backed by optional over current protection and GFCI, ensures total protection.
DIY	Do-It-Yourself kits - UTHKT, with detailed instruction manuals, makes the Under Floor Heating Kits very user-friendly.

Product Range

Catalog Reference No.	Length (M)	Watts (W)		
Undertile Heating Cable Single 10W/m @ 230V				
UTHCS-10W/115 UTHCS-10W/150 UTHCS-10W/170 UTHCS-10W/210 UTHCS-10W/225 UTHCS-10W/350 UTHCS-10W/400 UTHCS-10W/480 UTHCS-10W/560 UTHCS-10W/700 UTHCS-10W/820 UTHCS-10W/1040	11.5 15 17 21 22.5 29 35 40 48 56 70 82 104	115 150 170 210 225 290 350 400 480 560 700 820 1040		
UTHCS-10W/1140 UTHCS-10W/1250 UTHCS-10W/1450 UTHCS-10W/1700 UTHCS-10W/2000 UTHCS-10W/2400 UTHCS-10W/3000	114 125 145 171 195 242 297	1140 1250 1450 1700 2000 2400 3000		

Thermopads Standard Accessories - Thermostat

TS-PE-16 is a digital thermostat capable of switching on the heating system at predetermined times and can be programmed for one week.

Catalog Reference No.	Length (M)	Watts (W)			
Undertile Heating Cable Twin 10W/m @ 230V					
UTHCT-10W/115	11.5	115			
UTHCT-10W/140	14	140			
UTHCT-10W/170	17	170			
UTHCT-10W/210	21	210			
UTHCT-10W/225	22.5	225			
UTHCT-10W/290	29	290			
UTHCT-10W/350	35	350			
UTHCT-10W/400	40	400			
UTHCT-10W/480	48	480	S		
UTHCT-10W/560	56	560	ment		
UTHCT-10W/640	64	640	quire		
UTHCT-10W/700	70	700	fic re		
UTHCT-10W/760	76	760	speci		
UTHCT-10W/820	82	820	per s		
UTHCT-10W/1040	104	1040	ilt as		
UTHCT-10W/1140	114	1140	nq-u		
UTHCT-10W/1250	125	1250	Can also be custom-built as per specific requirements		
UTHCT-10W/1450	145	1450	pe c		
UTHCT-10W/1600	160	1600	also		
UTHCT-10W/1800	180	1800	Can		

- Note: 1. For Underfloor Heating Kits replace UTHCS by UTHCSKT and UTHCT by UTHCTKT in the above mentioned catalogue nos.
 - 2. For North America Range, Please contact us at info@thermopads.com